

# 26-S

*Ambulance Cot*

Code: 26-S



Rel. 050614

# 26-S



Safe patient transport without fatigue for operators. Smooth, simple and ergonomic operations when loading and unloading from an ambulance.

## MAIN FEATURES

- Aluminium construction provides strength and lightweighness guaranteeing maximum maneuverability during patient transport and during loading and unloading from the ambulance.
- The cot can be shortened by elevating the backrest and folding down the hinged, head-end frame: it maximizes cot mobility in confined spaces and in elevators.
- The legs, front and rear, are protected by polyethylene scuff guards against wear due to normal use of the cot during loading and unloading.
- The 26-S cot is equipped with an adjustable backrest, a shock frame for Trendelenburg position and 2 swing-down sidearms.
- Two 360° swivel rear wheels are equipped with integrated wheel locks that avoid the risk of accidental movements of the cot and maximize cot stability.
- The ABS panels are easy to remove for disinfection.
- The 26-S cot allows transport of isolette with the dedicated interface **ITC** ("Incubator Transport Interface").
- Conforms to EN 1865.
- Compatible with the ambulance fastener **SLAM** (tested EN 1789).

## SPECIFICATIONS

Length	1920 mm
Width	550 mm
Height	min. 240 mm - max. 800 mm
Weight (ABS panels included)	32 kg
Load Limit	181 kg

## ACCESSORIES

Description	Code
Kit for 26-S series cot (includes: 1 mattress 359-21, 1 417-1N restraint, 2 430-2-N restraints)	KIT-BLACK
Ambulance fastener (front antler anchorage included)	SLAM-26
514 OXY-CLIP Oxygen Cylinder Holder, removable	0085500
274 PAC-RAC stretcher table	0818952
IV-pole (folds along the side for easy storage)	513-10E
Incubator Transport Interface ITC (6 set fastener blocks included)	ITC

Rel. 050614

